


**OVERVIEW**



1. Power button	8. HDMI
2. USB-C 3.2 Gen 1	9. USB 3.2 Gen 1
3. USB 3.2 Gen 2	10. Optional port 1 (VGA is shown)
4. Headphone / microphone combo jack (3.5mm)	11. 2x USB 2.0
5. Power connector	12. Optional port 2 (serial is shown)
6. DisplayPort	13. Ethernet (RJ-45)
7. USB 3.2 Gen 1	

## PERFORMANCE

### Processor

#### Processor Family

AMD Athlon™ or AMD Ryzen™ 3 / 5 / 7 Processor

#### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Athlon Silver 3050GE	2	4	3.4GHz	3.4GHz	1MB L2 / 4MB L3	DDR4-2666	AMD Radeon™ Graphics
AMD Athlon Silver PRO 3125GE	2	4	3.4GHz	3.4GHz	1MB L2 / 4MB L3	DDR4-2666	AMD Radeon Graphics
AMD Athlon Gold PRO 3150GE	4	4	3.3GHz	3.8GHz	2MB L2 / 4MB L3	DDR4-2933	AMD Radeon Graphics
AMD Ryzen 3 3200GE	4	4	3.3GHz	3.8GHz	2MB L2 / 4MB L3	DDR4-2933	AMD Radeon Vega 8 Graphics
AMD Ryzen 3 4300GE	4	8	3.5GHz	4.0GHz	2MB L2 / 4MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 3 5300GE	4	8	3.6GHz	4.2GHz	2MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 3 PRO 4350GE	4	8	3.5GHz	4.0GHz	2MB L2 / 4MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 3 PRO 5350GE	4	8	3.6GHz	4.2GHz	2MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 5 4600GE	6	12	3.3GHz	4.2GHz	3MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 5 5600GE	6	12	3.4GHz	4.4GHz	3MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 5 PRO 3350GE	4	8	3.3GHz	3.9GHz	2MB L2 / 4MB L3	DDR4-2933	AMD Radeon Vega 11 Graphics
AMD Ryzen 5 PRO 4650GE	6	12	3.3GHz	4.2GHz	3MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 5 PRO 5650GE	6	12	3.4GHz	4.4GHz	3MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 7 4700GE	8	16	3.1GHz	4.3GHz	4MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 7 5700GE	8	16	3.2GHz	4.6GHz	4MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 7 PRO 4750GE	8	16	3.1GHz	4.3GHz	4MB L2 / 8MB L3	DDR4-3200	AMD Radeon Graphics
AMD Ryzen 7 PRO 5750GE	8	16	3.2GHz	4.6GHz	4MB L2 / 16MB L3	DDR4-3200	AMD Radeon Graphics

### Operating System

#### Operating System\*\*<sup>[1]</sup>

- Windows® 11 Pro
- Windows 11 Home
- Windows 11 Home Single Language
- Windows 11 DG Windows 10 Pro 64
- Windows 10 Pro 64
- Windows 10 Home 64
- Windows 10 Home 64 Single Language
- Windows 10 IoT Enterprise
- IGEL Linux

# ThinkCentre M75q Gen 2

- Ubuntu Linux
- No operating system

**Notes:**

1. Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, Human Presence Detection, etc.

## Graphics

### Graphics\*\*<sup>[1]</sup>

Graphics	Type	Memory	Connector	Max Resolution	Key Features
AMD Radeon Graphics	Integrated	Shared	1x HDMI®, 1x DisplayPort™, 1x optional port (VGA / 2nd DP / USB-C® / 2nd HDMI / dual DP)	3840x2160@30Hz or 2560x1440@60Hz(HDMI), 1920x1200@60Hz(VGA), 3840x2160(DP)@60Hz	DirectX® 12
AMD Radeon Vega 8 Graphics	Integrated	Shared	1x HDMI, 1x DisplayPort, 1x optional port (VGA / 2nd DP / USB-C / 2nd HDMI / dual DP)	3840x2160@30Hz or 2560x1440@60Hz(HDMI), 1920x1200@60Hz(VGA), 3840x2160(DP)@60Hz	DirectX 12
AMD Radeon Vega 11 Graphics	Integrated	Shared	1x HDMI, 1x DisplayPort, 1x optional port (VGA / 2nd DP / USB-C / 2nd HDMI / dual DP)	3840x2160@30Hz or 2560x1440@60Hz(HDMI), 1920x1200@60Hz(VGA), 3840x2160(DP)@60Hz	DirectX 12

**Notes:**

1. The information of integrated graphics are not applicable for the models with processor which has no integrated graphics inside (for the details, please refer to processor section)

## Monitor Support

### Monitor Support

Supports up to 3 independent displays via onboard ports (DisplayPort + HDMI) and optional ports (VGA / 2nd DP / 2nd HDMI / USB-C / 2x DP)

## Chipset

### Chipset

AMD PRO 500 chipset

## Memory

### Max Memory<sup>[1]</sup>

Up to 64GB DDR4-3200

### Memory Slots

Two DDR4 SO-DIMM slots, dual-channel capable

### Memory Type<sup>[2]</sup>

DDR4-3200

**Notes:**

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.
2. Installed memory is actually 3200MHz, but may run at 2666MHz, 2933MHz or 3200MHz depending on the memory support capability of processor

## Storage

### Storage Support<sup>[1]</sup>

Up to two drives, 1x 2.5" HDD + 1x M.2 SSD

- 2.5" HDD up to 1TB
- M.2 SSD up to 1TB

### Storage Type\*\*\*

Disk Type	Interface	RPM	Security
-----------	-----------	-----	----------

# ThinkCentre M75q Gen 2

2.5" SATA HDD	SATA 6Gb/s	5.4K	-
2.5" SATA HDD	SATA 6Gb/s	7.2K	-
M.2 2242 SSD	PCIe® NVMe®, PCIe 3.0 x2	-	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	Opal

**Notes:**

1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

## Removable Storage

**Optical\*\***

- DVD-ROM, slim (9.0mm), via USB external ODD box
- DVD burner (DVD±RW), slim (9.0mm), via USB external ODD box
- None

## Multi-Media

**Audio Chip**

High Definition (HD) Audio, Realtek® ALC222 codec

**Speakers**

Single speaker, 1.5W x1

## Power Supply

**Power Supply\*\***

Power	Type	Efficiency	Key Features
65W	Adapter	89%	Autosensing
90W	Adapter	89%	Autosensing

## DESIGN

### Input Device

**Keyboard\*\***

- Lenovo Calliope Keyboard (USB connector), black
- Lenovo Calliope Wireless Keyboard, black
- Lenovo Traditional Keyboard (USB connector), black
- No keyboard

**Mouse\*\***

- Lenovo Calliope Mouse (USB connector), black
- Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black
- Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black
- No mouse

## Mechanical

**Form Factor**

Tiny (1L)

**Dimensions (WxDxH)<sup>[1]</sup>**

Models	Dimensions
Tiny only	179 x 183 x 34.5 / 37 mm with rubber feet (7.05 x 7.2 x 1.36 / 1.5 inches with rubber feet)

**Packaging Dimensions (WxDxH)**

- Tiny only: 141 x 268 x 490 mm (5.55 x 10.55 x 19.29 inches)
- With VESA mount & ODD box: 166 x 268 x 490 mm (6.54x 10.55 x 19.29 inches)

**Weight<sup>[2]</sup>**

Models	Weight
--------	--------

Tiny only	1.25 kg (2.76 lbs)
-----------	--------------------

**Packaging Weight**

- With VESA mount & ODD box: 3.575 kg (7.88 lbs)
- Tiny only: 2.848 kg (6.28 lbs)

**Case Color**

Black

**Bays**

1x 2.5" disk bay

**Expansion Slots**

- One M.2 slot (for WLAN)
- One M.2 slot (for SSD)

**EOU**

(Optional) toolless chassis open (toolless chassis screw required) and toolless M.2 SSD, HDD, memory assembly / removal

**Stand**

- Vertical stand
- No stand

**Mounting**

- VESA mount bracket kit, supports VESA mount 75mm and 100mm
- None

**Notes:**

1. The system dimensions may vary depending on configurations.
2. The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

## CONNECTIVITY

### Network

**Onboard Ethernet**

- Gigabit Ethernet, Realtek RTL8111HN, 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Realtek RTL8111FP, 1x RJ-45, supports DASH and Wake-on-LAN

**WLAN + Bluetooth<sup>®</sup>\*<sup>[1]</sup>**

- Realtek RTL8822BE, 802.11ac Dual Band 1x1 Wi-Fi<sup>®</sup> + Bluetooth 4.2, M.2 card
- Realtek RTL8822CE, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Intel Wireless-AC 9260, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- Realtek Wi-Fi 6 RTL8852AE, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- Intel Wi-Fi 6 AX200, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- No WLAN and Bluetooth

**Notes:**

1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.

### Ports<sup>[1]</sup>

**Front Ports**

- 1x USB 3.2 Gen 2 (Always On and fast charge)
- 1x USB-C 3.2 Gen 1
- 1x headphone / microphone combo jack (3.5mm)

**Rear Ports<sup>[2]</sup>**

- 1x HDMI
- 1x DisplayPort
- 2x USB 2.0
- 2x USB 3.2 Gen 1
- 1x Ethernet (RJ-45)

**Optional Rear Ports<sup>\*\*\*</sup>**

- Optional port 1 (one of VGA / 2nd DisplayPort / 2nd HDMI / serial / USB-C 3.2 Gen 1 with DisplayPort function)
- 2x USB 3.2 Gen 1 (occupies port 1 and 2)

# ThinkCentre M75q Gen 2

- 4x USB 3.2 Gen 1 (share one USB 3.2 Gen 1 bandwidth, occupy port 1 and 2)
- 2x DisplayPort (occupies port 1 and 2)
- Optional port 2 (serial)
- 1x parallel

## Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.  
USB 2.0: 480 Mbit/s;  
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;  
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;  
USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;  
USB4 40Gbps (USB 40Gbps): 40 Gbit/s;  
Thunderbolt™ 3/4: 40 Gbit/s
2. For video ports on discrete graphics, please see graphics section

## Monitor Cable

### Monitor Cable\*\*\*

- VGA Cable Tiny
- HDMI to HDMI cable (1.5m)
- HDMI to VGA dongle
- DP to VGA dongle
- DP to VGA cable (1.5M)
- DP to dual DP dongle
- DP to DVI-D dongle
- DP to HDMI 1.4 dongle
- No monitor cable

## SECURITY & PRIVACY

### Security

#### Security Chip

Discrete TPM 2.0, TCG certified

#### Physical Locks

Kensington® Security Slot™, 3 x 7 mm

#### Chassis Intrusion Switch

Chassis intrusion switch

#### BIOS Security

- Administrator password
- Power-on password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Individual USB port disablement

## MANAGEABILITY

### System Management

#### System Management

- DASH 1.2
- Non-DASH

## SERVICE

### Warranty<sup>[1]</sup>

#### Base Warranty\*\*

- 1-year courier or carry-in service
- 1-year limited onsite service
- 3-year limited onsite service

- No base warranty

---

**Notes:**

1. The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to <https://smartfind.lenovo.com/>. To learn more details of warranty policy, please access <https://pcsupport.lenovo.com/warranty>.

## ENVIRONMENTAL

### Operating Environment

#### Temperature

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

#### Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

#### Altitude

- Operating: 0 m (0 ft) to 3048 m (10,000 ft)
- Storage: 0 m (0 ft) to 12192 m (40,000 ft)

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications

- (Optional) EPEAT™ Gold
- ENERGY STAR® 8.0
- ErP Lot 3
- TCO Certified
- RoHS compliant

---

**Notes:**

1. The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

### Other Certifications

#### Mil-Spec Test

MIL-STD-810H military test passed

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Feature with \*\*\* means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.




AMD



AMD



AMD



AMD



AMD



AMD