

OVERVIEW



|   |  |
|---|--|
| 1. USB-A (USB 5Gbps)                            | 5. Thunderbolt 4                             |
| 2. Ethernet (RJ-45)                             | 6. USB-A (USB 10Gbps), Always On             |
| 3. Kensington Nano Security Slot                | 7. HDMI                                      |
| 4. USB-C (USB 20Gbps), with USB PD 3.0 & DP 1.4 | 8. Headphone / microphone combo jack (3.5mm) |

PERFORMANCE

Processor

Processor Family

Intel® U or H Series Core™ Ultra 5 / 7 Processor (Series 1)

Processor\*\*

| Processor Name     | Cores                                 | Threads | Base Frequency                                  | Max Frequency                                   | Cache | Processor Graphics                  | AI Engine       |
|--------------------|---------------------------------------|---------|---|---|-------|-------------------------------------|-----------------|
| Core™ Ultra 5 125H | 14 (4 P-core + 8 E-core + 2 LPE-core) | 18      | P-core 1.2GHz / E-core 700MHz / LPE-core 700MHz | P-core 4.5GHz / E-core 3.6GHz / LPE-core 2.5GHz | 18MB  | Intel® Arc™ Graphics <sup>[1]</sup> | Intel® AI Boost |
| Core™ Ultra 5 125U | 12 (2 P-core + 8 E-core + 2 LPE-core) | 14      | P-core 1.3GHz / E-core 800MHz / LPE-core 700MHz | P-core 4.3GHz / E-core 3.6GHz / LPE-core 2.1GHz | 12MB  | Intel® Graphics                     | Intel® AI Boost |
| Core™ Ultra 5 135U | 12 (2 P-core + 8 E-core + 2 LPE-core) | 14      | P-core 1.6GHz / E-core 1.1GHz / LPE-core 700MHz | P-core 4.4GHz / E-core 3.6GHz / LPE-core 2.1GHz | 12MB  | Intel® Graphics                     | Intel® AI Boost |
| Core™ Ultra 7 155H | 16 (6 P-core + 8 E-core + 2 LPE-core) | 22      | P-core 1.4GHz / E-core 900MHz / LPE-core 700MHz | P-core 4.8GHz / E-core 3.8GHz / LPE-core 2.5GHz | 24MB  | Intel® Arc™ Graphics <sup>[2]</sup> | Intel® AI Boost |
| Core™ Ultra 7 155U | 12 (2 P-core + 8 E-core + 2 LPE-core) | 14      | P-core 1.7GHz / E-core 1.2GHz / LPE-core 700MHz | P-core 4.8GHz / E-core 3.8GHz / LPE-core 2.1GHz | 12MB  | Intel® Graphics                     | Intel® AI Boost |
| Core™ Ultra 7 165U | 12 (2 P-core + 8 E-core + 2 LPE-core) | 14      | P-core 1.7GHz / E-core 1.2GHz / LPE-core 700MHz | P-core 4.9GHz / E-core 3.8GHz / LPE-core 2.1GHz | 12MB  | Intel® Graphics                     | Intel® AI Boost |

Notes:

[1], [2] Intel® Arc™ Graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

Operating System

Operating System\*\*

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Ubuntu Linux<sup>[1]</sup>
- No preload operating system

Notes:

[1] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics\*\*

| Graphics                            | Type       | Memory | TGP           | Key Features  |
|-------------------------------------|------------|--------|---------------|---------------|
| Intel® Arc™ Graphics <sup>[1]</sup> | Integrated | Shared | Share CPU TDP | DirectX® 12.1 |
| Intel® Graphics                     | Integrated | Shared | Share CPU TDP | DirectX® 12.1 |

Notes:

[1] Intel® Arc™ Graphics only available on select H-series Intel® Core™ Ultra processor powered systems with at least 16GB of system memory in a dual-channel configurations, otherwise it will function as Intel® Graphics.

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI®, USB-C®, and Thunderbolt™)

- HDMI® supports up to 4K@60Hz
- USB-C® supports up to 5K@60Hz
- Thunderbolt™ supports up to 8K@60Hz

Chipset

Chipset  
Intel® SoC (System on Chip) platform

Memory

Max Memory<sup>[1]</sup>  
Up to 64GB DDR5-5600

Memory Slots  
Two DDR5 SO-DIMM slots, dual-channel capable

Memory Type  
DDR5-5600

Notes:  
[1] Maximum memory is only to test technical readiness of notebook. Available memory to sell would vary.

Storage

Storage Support<sup>[1]</sup>  
Up to two drives, 2x M.2 SSD

- M.2 2242 SSD up to 1TB
- M.2 2280 SSD up to 1TB

Storage Slot  
Two M.2 slots

- One M.2 2242 PCIe® 4.0 x4 slot
- One M.2 2280 PCIe® 4.0 x4 slot

Storage Type

| Disk Type    | Interface                 | Offering            | Security |
|--------------|---------------------------|---------------------|----------|
| M.2 2242 SSD | PCIe® NVMe®, PCIe® 4.0 x4 | 256GB / 512GB / 1TB | Opal 2.0 |

Notes:  
[1] The system supports dual SSD via two M.2 slots, but Lenovo® only offers one M.2 2242 SSD configuration and M.2 2280 slot for user self-extension.

Removable Storage

Card Reader  
No card reader

Multi-Media

Audio Chip  
High Definition (HD) Audio, Senary SN6141 codec

Speakers  
Stereo speakers, 2W x2, Dolby® Atmos®, audio by HARMAN

Microphone  
Dual-microphone array with smart noise-cancelling

Camera\*\*

- FHD 1080p + IR hybrid, with privacy shutter, fixed focus
- FHD 1080p, with privacy shutter, fixed focus
- HD 720p, with privacy shutter, fixed focus

Battery

Battery\*\*

- Integrated Li-Polymer 47Wh battery, supports Rapid Charge Pro (charge up to 50% in 30min)
- Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Battery Life<sup>[1]</sup>

Configuration 1 (max battery life)  
MobileMark® 25: up to 11.8 hr with 793 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 11.68 hr / 20.9 hr @200nits  
Local video playback: up to 20.24 hr @150nits

Alternate configuration 2  
MobileMark® 25: up to 11.75 hr with 590 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 11.22 hr / 20.23 hr @200nits  
Local video playback: up to 19.4 hr @150nits

Alternate configuration 3  
MobileMark® 25: up to 9.33 hr with 591 performance score @250nits  
JEITA-BAT 3.0 (Video/Idle): up to 9.22 hr / 16.5 hr @200nits  
Local video playback: up to 15.66 hr @150nits

Notes:

<sup>[1]</sup> Configuration 1 (max battery life): WUXGA (non-touch), Intel® Core™ Ultra 5 125U, 8GB+8GB DDR5, Win 11, 57Wh battery, best power efficiency power mode  
Alternate configuration 2: WUXGA (touch), Intel® Core™ Ultra 5 135U, 16GB DDR5, Win 11, 57Wh battery, best power efficiency power mode  
Alternate configuration 3: WUXGA (touch), Intel® Core™ Ultra 5 135U, 16GB DDR5, Win 11, 47Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using [MobileMark® 25](#), JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.  
Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.  
The maximum capacity of the battery will decrease with time, ambient temperature and use.  
Refer to [Microsoft® link](#) for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter<sup>\*\*[1]</sup>

- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

<sup>[1]</sup> AC adapter offerings depend on the country.

DESIGN

Display

Display<sup>\*\*</sup>

| Size | Resolution        | Touch       | Type               | Brightness | Surface    | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features                  |
|------|-------------------|-------------|--------------------|------------|------------|--------------|----------------|-------------|--------------|-------------------------|-------------------------------|
| 14"  | WUXGA (1920x1200) | None        | IPS <sup>[1]</sup> | 300nits    | Anti-glare | 16:10        | 800:1          | 45% NTSC    | 60Hz         | 85°/85°/85°/85°         | TÜV Low Blue Light (Software) |
| 14"  | WUXGA (1920x1200) | Multi-touch | IPS <sup>[2]</sup> | 300nits    | Anti-glare | 16:10        | 800:1          | 45% NTSC    | 60Hz         | 85°/85°/85°/85°         | TÜV Low Blue Light (Software) |
| 14"  | 2.2K (2240x1400)  | None        | IPS <sup>[3]</sup> | 300nits    | Anti-glare | 16:10        | 1500:1         | 100% sRGB   | 60Hz         | 85°/85°/85°/85°         | Eyesafe® Certified 2.0        |

Touchscreen

- On-cell multi-touch, supports 10-point touch

- Non-touch

Notes:

[1], [2], [3] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

- LED backlight
- Non-backlight

UltraNav™

TrackPoint® pointing device, double-tap to open the TrackPoint® Quick Menu  
Mylar® surface multi-touch touchpad, 56 x 115 mm (2.24 x 4.53 inches)

Mechanical

Dimensions (WxDxH)<sup>[1]</sup>

| Models   | Dimensions  |
|--|---|
| Models with aluminium (top) and aluminium (bottom) | Starting at 313 x 219.3 x 17.99 mm (12.32 x 8.63 x 0.71 inches) |
| Models with aluminium (top) and PC-ABS (bottom)    | Starting at 313 x 219.3 x 18.59 mm (12.32 x 8.63 x 0.73 inches) |

Weight<sup>[2]</sup>

| Models   | Weight                         |
|--|--------------------------------|
| Models with aluminium (top) and aluminium (bottom) | Starting at 1.44 kg (3.17 lbs) |
| Models with aluminium (top) and PC-ABS (bottom)    | Starting at 1.42 kg (3.14 lbs) |

Case Color\*\*

- Arctic grey
- Graphite black

Case Material\*\*

- Aluminium (top), PC-ABS (bottom)
- Aluminium (top), aluminium (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet\*\*

- Gigabit Ethernet, Intel® Ethernet Connection I219-LM (vPro® models), 1x RJ-45, supports Wake-on-LAN
- Gigabit Ethernet, Intel® Ethernet Connection I219-V (non-vPro® models), 1x RJ-45, supports Wake-on-LAN

WLAN + Bluetooth®\*\*<sup>[1]</sup>

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 card
- Realtek® Wi-Fi® 6 RTL8852BE, 802.11ax Dual Band 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card
- Intel® Wi-Fi® 6 AX201, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.2, M.2 Card
- Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card<sup>[2]</sup>
- Realtek® Wi-Fi® 6E RTL8852CE, 802.11ax Dual Band 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card<sup>[3]</sup>
- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 Card<sup>[4]</sup>

WWAN

No support

SIM Card

No physical SIM card inbox

#### NFC

No support

Notes:

[1] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2], [3], [4] Wi-Fi® 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 operation requires Windows® 11. For more information please see [General Bluetooth® Support Information on Microsoft®](#).

## Ports<sup>[1]</sup>

### Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 10Gbps / USB 3.2 Gen 2), Always On
- 1x USB-C® (USB 20Gbps / USB 3.2 Gen 2x2), with USB PD 3.0 and DisplayPort™ 1.4
- 1x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 3.0 and DisplayPort™ 2.1
- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

## Docking

### Docking

Various docking solutions supported via Thunderbolt™ or USB-C®.

For more compatible docking solutions, please visit [Docking for ThinkPad® E14 Gen 6 \(Intel®\)](#)

## SECURITY & PRIVACY

## Security

### Security Chip

Discrete TPM 2.0, TCG certified, FIPS 140-2 certified

### Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

### Smart Card Reader

No smart card reader

### Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

### BIOS Security

- Power-on password
- Supervisor password
- NVMe® password
- Self-healing BIOS

### Other Security

- (Optional) IR camera for Windows® Hello (facial recognition)

- Camera privacy shutter

## MANAGEABILITY

### System Management

#### System Management

- Intel® vPro® Enterprise<sup>[1]</sup>
- Non-vPro®

Notes:

[1] Intel® vPro® offers a superset of DASH's defined capabilities.

## SERVICE

### Warranty

#### Base Warranty\*\*

- 1-year mail-in service
- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- No base warranty

## ENVIRONMENTAL

### Sustainability

#### Material

25% PCC recycled plastic used in the battery  
30% PCC recycled plastic used in speaker enclosure  
90% PCC recycled plastic used in standard 65W adapter  
Plastic free packaging  
Dry-pressed bamboo & sugarcane fiber Cushions  
FSC Certified paper in packaging

### Operating Environment

#### Temperature<sup>[1]</sup>

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F ) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

#### Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

## ACCESSORIES

### Bundled Accessories

#### Bundled Accessories<sup>[1]</sup>

- Lenovo® 15.6" laptop casual toplayer, polyester
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for ThinkPad® E14 Gen 6 \(Intel®\)](#)

## CERTIFICATIONS

### Green Certifications<sup>[1]</sup>

#### Green Certifications<sup>[2]</sup>

- ENERGY STAR® 8.0
- EPEAT™ Gold Registered<sup>[3]</sup>
- ErP Lot 6
- ErP Lot 26
- RoHS compliant
- TCO Certified 9.0

#### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.

[2] EPEAT™ registration and ENERGY STAR® certification are dependent on system OS. Please visit [epeat.net](#) and [energystar.gov](#) for more information.

[3] EPEAT™ is registered where applicable, please see [epeat.net](#) for registration status by country.

### Other Certifications

#### Mil-Spec Test

Work in progress

#### Other Certifications

- (Optional) Eyesafe® Certified 2.0
- (Optional) TÜV Rheinland® Low Blue Light (Hardware Solution)
- (Optional) TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.






Microsoft



Microsoft



Microsoft



Microsoft



Microsoft



Microsoft